



DEVOE PAINT®  
 WONDER-PRO™  
 Interior/Exterior Eggshell  
 Acrylic Latex Enamel  
 DR218XX

FINISHES  
 PAINTING (09900)  
 9

DESCRIPTION

A quality latex eggshell wall, ceiling and trim enamel formulated to meet the requirements of painters, building contractors and building managers. This eggshell enamel features high-hide, easy spatter-free application, quick dry and recoat. Provides a durable and scrubbable eggshell finish.

FEATURES

- Easy application
- Fast drying
- Good dry hide
- Durable and washable
- Easy soap and water clean-up
- Low odor
- Low VOC

COMPOSITION

- Vinyl-Acrylic Resin
- Titanium Dioxide and Extender Pigments
- Not manufactured with lead or mercury containing materials.

SPECIFICATION DATA

**Color:**  
 White, ready mix & custom colors

**Finish:**  
 Eggshell, 5-12 units @ 60°

**Clean-up Solvent:**  
 Soap & water

**Density:**  
 10.36 lbs/gal (1.24 kg/L)

**VOC:**  
 0.40 lbs/gal (48 g/L)

**Solids:**  
 Volume - 32% +/- 1%  
 Weight - 44% +/- 1%

**Practical Coverage:**  
 Apply at 400 sq ft/gal (10 m<sup>2</sup>/L).  
 Actual coverage may vary depending on substrate and application method.

**Flame Spread Rating:**  
 Class A (0-25) over non-combustible surfaces

**Flash Point:**  
 None

**Dry Time 77°F (25°C) & 50% RH:**  
 To touch – 30-60 minutes  
 To recoat – 2-4 hours



9  
 FINISHES  
 PAINTING (09900)

## SURFACE PREPARATION

All surfaces must be sound, dry, clean and free of oil, grease, dirt, mildew, form release agents, curing compounds, loose and flaking paint and other foreign substances.

**NEW SURFACES:** **Drywall** - Prime with this product or latex primer DR 50801. **Wood** - Interior, set nails and fill holes with latex spackle. Sand smooth. Dust clean. Self-prime or prime with latex primer DR 51701. Do not use this product with lacquer undercoats. Exterior, spot prime pine knots with latex primer DR 1502. Prime entire surface with latex primer DR 1502. **Concrete, Plaster and Masonry** - Cure at least 30 days before painting. pH must be 10.0 or lower. Roughen slick poured or precast concrete and remove sealers by chemical cleaning or abrasive method such as sandsweeping. Rinse thoroughly with water and allow to dry. Remove loose aggregate. Prime interior concrete or plaster with latex primer DR 51801. Prime exterior concrete with latex primer DR 1502. Fill concrete block with latex block filler DV 52903, then prime interior block with latex primer DR 51801 or prime exterior block with latex primer DR 1502. **Steel** - Prime with waterborne metal primer

DP 8502. **Galvanized Metal and Aluminum** - Prime with waterborne metal primer DP 8502.

**PREVIOUSLY PAINTED SURFACES:** Wash to remove contaminants. Rinse thoroughly with water and allow to dry. Dull glossy areas by light sanding. Remove sanding dust. Remove loose paint. Prime bare areas with primer specified under **NEW SURFACES**.

**WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear an NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).**

## DIRECTIONS FOR USE

**TINTING:** Tint the appropriate base with ICI Paints Colorants.

**SPREADING RATE:** Apply at 400 sq ft/gallon (10 m<sup>2</sup>/L). Actual coverage may vary depending on substrate and application method. For best hiding, tint primers towards finish coat color. Certain shades of yellow, orange, pink and red may require multiple coats.

**APPLICATION:** Mix thoroughly before use. May be applied by brush, roller or spray. No thinning required. For airless spray, use a .015" tip. Adjust pressure as needed. Do not apply when the surface or air temperature is below 50°F (10°C). Provide good ventilation

and warmth for normal drying.

**DRYING TIME:** At 77°F (25°C) and 50% R.H., dries to touch in 30-60 minutes and to recoat in two to four hours. Low temperature, high humidity, thick films or poor ventilation will increase these times.

**CLEAN-UP:** Clean immediately with warm, soapy water.

**WASHING INSTRUCTIONS:** Allow at least seven days after application before washing. Use non-abrasive, mild detergent and cellulose sponge.

## PRECAUTIONS

**WARNING! CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION. MAY BE HARMFUL IF SWALLOWED. WHEN TINTED, CONTAINS ETHYLENE GLYCOL WHICH CAN CAUSE SEVERE KIDNEY DAMAGE WHEN INGESTED AND HAS BEEN SHOWN TO CAUSE BIRTH DEFECTS IN LABORATORY ANIMALS. USE ONLY WITH ADEQUATE VENTILATION. KEEP OUT OF THE REACH OF CHILDREN.** For emergency information call (800) 545-2643. **Note: These warnings encompass the product series. Prior to use, read and follow product-specific MSDS and label information.** If sanding, wear a dust mask to avoid breathing of sanding dust. Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. Avoid contact with eyes and skin. If you experience eye watering, headaches, or dizziness, leave the area. If properly used, a respirator may offer additional protection. Obtain professional advice before using. Close container after each use. **FIRST AID:** For skin contact, wash thoroughly with soap and water. If any product remains, gently rub with petroleum jelly, vegetable or mineral/baby oil then wash again with soap and water. Repeat as needed. Remove contaminated clothing. For eye contact, flush immediately with plenty of water for at least 15 minutes. **Get medical attention.** If swallowed, **get medical attention immediately.** If inhalation causes discomfort, remove to fresh air. If discomfort persists or breathing difficulty occurs, get medical attention. **KEEP FROM FREEZING.**

DS10-1005

## SHIPPING

**FREIGHT CLASSIFICATION:**  
Paint, Freezable

**PACKAGING:**  
1 gallon (3.785)  
5 gallons (18.925 L)

**FLASH POINT:**  
None



ICI Paints, Strongsville, Ohio 44136



1-888-681-6353 • [www.devoepaint.com](http://www.devoepaint.com)

**LIMITATION OF LIABILITY** To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance but are subject to change without prior notice. We guarantee our product to conform to the specifications contained herein. WE MAKE NO OTHER WARRANTY OR GUARANTEE OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSE. Liability, if any, is limited to replacement of the product or refund of the purchase price. LABOR OR COST OF LABOR AND OTHER CONSEQUENTIAL DAMAGES ARE HEREBY EXCLUDED.