



WONDER-TONES™

Interior Eggshell Latex Enamel DRN34XX

FINISHES
PAINTING (09900)

9

DESCRIPTION

Our best quality latex eggshell acrylic enamel for use on interior walls and trim. The low luster sheen minimizes imperfections and yet provides a more washable and durable finish than conventional latex flat wall paints. Specially formulated to meet the special requirements of painters, building contractors, interior decorators, architects and building managers. Provides very good touch-up, excellent coverage and application properties. Ideal for use on interior walls where a durable eggshell finish is required. May be used over properly prepared drywall, plaster, masonry, primed metal and wood in offices, schools, hospitals, institutions, residential and commercial buildings. Meets Master Painters Institute #44 specifications.

FEATURES

- Our Best
- Durable, Eggshell Finish
- Very Good Touchup
- Washes Beautifully
- High Hiding
- Scrub resistant
- Low VOC
- MPI Approved, Category #44
- Meets LEED for low VOC Paint (USGBC)

COMPOSITION

- Vinyl-Acrylic Resin
- Titanium Dioxide and Extender Pigments
- Not manufactured with lead or mercury containing materials.

SPECIFICATION DATA

Color:

Tintable white & custom colors

Finish:

Eggshell, 5-12 units @ 60°

Clean-up Solvent:

Soap & water

Density:

10.50 lbs/gal (1.26 kg/L)

VOC:

50 g/L (0.42 lbs/gal) maximum

Solids:

Volume - 36% +/- 1%

Weight - 49% +/- 1%

Practical Coverage:

Apply at 300-400 sq ft/gal (7-10 m²/L).

Actual coverage may vary depending on substrate and application method.

Flame Spread Rating:

Class A (0-25) over non-combustible surfaces

Flash Point:

None

Dry Time 77°F (25°C) & 50% RH:

To touch – 1 hour

To recoat – 4 hours

Shelf Life:

1 year minimum - unopened



FINISHES
PAINTING (09900)

9

SURFACE PREPARATION

All surfaces must be sound, dry, clean and free of oil, grease, dirt, mildew, form release agents, curing compounds, loose and flaking paint and other foreign substances.

NEW SURFACES: **Drywall** - Prime with this paint or latex wall primer DR50801. **Concrete, Masonry and Plaster** - Cure at least 30 days before painting. pH must be 10.0 or lower. Roughen slick poured or precast concrete and remove sealers by chemical cleaning or abrasive method such as sandsweeping. Rinse thoroughly with water and allow to dry. Must be internally dry. Remove loose aggregate. Prime concrete with this paint or all-purpose primer DR51801. Fill concrete block with latex block filler DV52903. Prime plaster with all-purpose primer DR51801. **Wood** - Set nails, fill with latex spackle. Sand smooth. Dust clean. Prime with latex wood primer DR51701 or alkyd wood primer DR8801. **Steel** - Prime with waterborne metal primer DP85XX or solventborne metal primer DP13201. **Galvanized Metal and Aluminum** - Prime with

waterborne metal primer DP85XX or solventborne metal primer DP13201.

PREVIOUSLY PAINTED SURFACES: Wash to remove contaminants. Rinse thoroughly with water and allow to dry. Remove loose paint. Prime bare areas with primer specified under **NEW SURFACES**.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear an NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

DIRECTIONS FOR USE

TINTING: Tint the appropriate base with ICI Paints Colorants.

SPREAD RATE: Apply at 300-400 sq. ft. per gallon (7-10 m²/L) depending on surface texture and porosity. For best hiding, tint primers toward finish coat color. Certain shades of yellow, orange, pink and red may require multiple coats.

APPLICATION: Mix thoroughly before use. May be applied by brush (synthetic), roller (3/8" to 1/2" nap) or spray. No thinning required. For airless spray, use a .015"-.017" tip. Adjust pressure as needed. Do not apply when the surface or air temperature is below 50°F (10°C). Provide good

ventilation and warmth for normal drying.

DRYING TIME: At 77°F (25°C) and 50% R.H., dries to touch in one hour and to recoat in four hours. Low temperature, high humidity, thick films or poor ventilation will increase these times.

CLEAN-UP: Clean immediately with warm, soapy water.

WASHING INSTRUCTIONS: Allow at least seven days after application before washing. Use non-abrasive, mild detergent and cellulose sponge.

PRECAUTIONS

WARNING! CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION. MAY BE HARMFUL IF SWALLOWED. WHEN TINTED, CONTAINS ETHYLENE GLYCOL WHICH CAN CAUSE SEVERE KIDNEY DAMAGE WHEN INGESTED AND HAS BEEN SHOWN TO CAUSE BIRTH DEFECTS IN LABORATORY ANIMALS. USE ONLY WITH ADEQUATE VENTILATION. KEEP OUT OF THE REACH OF CHILDREN. For emergency information call (800) 545-2643. **Note: These warnings encompass the product series. Prior to use, read and follow product-specific MSDS and label information.** If sanding, wear a dust mask to avoid breathing of sanding dust. Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. Avoid contact with eyes and skin. If you experience eye watering, headaches, or dizziness, leave the area. If properly used, a respirator may offer additional protection. Obtain professional advice before using. Close container after each use. **FIRST AID:** For skin contact, wash thoroughly with soap and water. If any product remains, gently rub with petroleum jelly, vegetable or mineral/baby oil then wash again with soap and water. Repeat as needed. Remove contaminated clothing. For eye contact, flush immediately with plenty of water for at least 15 minutes. **Get medical attention.** If swallowed, **get medical attention immediately.** If inhalation causes discomfort, remove to fresh air. If discomfort persists or breathing difficulty occurs, get medical attention. **KEEP FROM FREEZING.** DS10-1005

SHIPPING

FREIGHT CLASSIFICATION:
Paint, Freezable

PACKAGING:
4 quart (0.9168 L)
1 gallon (3.785 L)
5 gallons (18.925 L)

FLASH POINT:
None



ICI Paints, Strongsville, Ohio 44136



1-888-681-6353 • www.devoepaint.com

LIMITATION OF LIABILITY To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance but are subject to change without prior notice. We guarantee our product to conform to the specifications contained herein. WE MAKE NO OTHER WARRANTY OR GUARANTEE OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSE. Liability, if any, is limited to replacement of the product or refund of the purchase price. LABOR OR COST OF LABOR AND OTHER CONSEQUENTIAL DAMAGES ARE HEREBY EXCLUDED.